




DIMENSIONS



Accessories



OPTIONAL MOUNTING
ACCESSORY



ADD-ON BEZEL

Awards



reddot design award
winner 2015



PRODUCT

Name	SWAP M UL 2700K G
Reference	U2122210G
Color	Gold
RAL	1036
Category	CEILING RECESSED

MOUNTING ACCESSORY / DRIVER

Mounting Accessory / Driver	Mandatory, not included. See next page
Model	REMOTE BOX 1.8-6.2W 110mA
Reference	U1000107

LIGHT SOURCE

Type	LED
Gross luminous flux	477 Lm
Color temperature	2700 K
Chromatic stability	MacAdam Step 2
Color Rendering Index	CRI>90
Power	3.6 W
Current	110 mA
Efficacy	133 Lm/W
LED lifespan	L90B10>55.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	77%
Delivered luminous flux	367 Lm
Light beam angle	42°

LIGHTING FIXTURE | ELECTRICAL DATA

Power values of the system	6 W
Voltage	120-277 V
Frequency	50/60 Hz
Dimming	0-10V


OTHER DATA

IC Rated	Yes
Environmental location	DAMP

Swap is a ceiling recessed LED spotlight whose main features are its minimalist aspect, its perfect integration into the ceiling, and considerable visual comfort, thanks to the small reflector that is set back with respect to the ceiling plane. When it is switched on, its matte finish shade generates an attractive effect, a discrete circle of light. It includes an add-on bezel that can be used optionally to cover larger recess diameters.



DIMENSIONS



Accessories



OPTIONAL MOUNTING
ACCESSORY



ADD-ON BEZEL

Awards



reddot design award
winner 2015




Recess measurements	Ø2.95 in Ø75 mm
Weight	0.28 lb 125 gr
Packaged weight	0.36 lb 165 gr
Packaging dimensions	3.98x4.06x3.90 in 101x103x99 mm
Materials	Aluminium / Polycarbonate

OTHER DATA



Swap is a ceiling recessed LED spotlight whose main features are its minimalist aspect, its perfect integration into the ceiling, and considerable visual comfort, thanks to the small reflector that is set back with respect to the ceiling plane. When it is switched on, its matte finish shade generates an attractive effect, a discrete circle of light. It includes an add-on bezel that can be used optionally to cover larger recess diameters.


Mandatory / Not Included




PRODUCT	
Model	REMOTE BOX 1.8-6.2W 110mA
Driver	Included: EVERLINE - PW series or similar
Reference	U1000107
IC Rated	Yes
Dimming	0-10V
Size	7.48 x 3.78 x 1.35 in 190 x 94 x 34 mm
Weight	1.89 lb 860 gr
Packaged weight	2.01 lb 915 gr
Packaging dimensions	9.53 x 4.13 x 1.54 in 242 x 105 x 39 mm
Nº Luminaires	1
LED - Driver Distance	18 AWG - 447 ft (350 mA) / 224 ft (700 mA)
	16 AWG - 711 ft (350 mA) / 356 ft (700 mA)
	14 AWG - 1132 ft (350 mA) / 566 ft (700 mA)
INPUT CHARACTERISTICS	
Input Voltage	120-277 V
Frequency	50/60 Hz
OUTPUT CHARACTERISTICS	
Output Voltage	16 - 56 V
Output Current	110 mA
Output Power	1.8 - 6.2 W



POLAR DIAGRAM



CONICAL DIAGRAM




UGR

Glare Evaluation According to UGR												
ρ Ceiling		70	70	50	50	30	70	70	50	50	30	30
ρ Walls		50	30	50	30	30	50	30	50	30	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
2H	2H	12.9	13.7	13.2	13.9	14.1	12.9	13.7	13.2	13.9	14.1	14.1
	3H	14.7	15.4	15.0	15.7	15.9	14.7	15.4	15.0	15.7	15.9	15.9
	4H	15.5	16.2	15.8	16.5	16.7	15.5	16.2	15.8	16.5	16.7	16.7
	6H	16.3	16.9	16.6	17.2	17.5	16.3	16.9	16.6	17.2	17.5	17.5
	8H	16.6	17.2	17.0	17.5	17.8	16.6	17.2	17.0	17.5	17.8	17.8
	12H	17.0	17.5	17.3	17.9	18.2	17.0	17.5	17.3	17.9	18.2	18.2
4H	2H	13.5	14.2	13.8	14.4	14.7	13.5	14.2	13.8	14.4	14.7	14.7
	3H	15.6	16.1	15.9	16.4	16.7	15.6	16.1	15.9	16.4	16.7	16.7
	4H	16.5	17.0	16.9	17.4	17.7	16.5	17.0	16.9	17.4	17.7	17.7
	6H	17.5	17.9	17.9	18.2	18.6	17.5	17.9	17.9	18.2	18.6	18.6
	8H	17.9	18.3	18.3	18.7	19.1	17.9	18.3	18.3	18.7	19.1	19.1
	12H	18.3	18.7	18.8	19.1	19.5	18.3	18.7	18.8	19.1	19.5	19.5
8H	4H	16.9	17.3	17.3	17.7	18.1	16.9	17.3	17.3	17.7	18.1	18.1
	6H	18.0	18.3	18.5	18.8	19.2	18.0	18.3	18.5	18.8	19.2	19.2
	8H	18.6	18.9	19.1	19.3	19.8	18.6	18.9	19.1	19.3	19.8	19.8
	12H	19.2	19.4	19.7	19.9	20.4	19.2	19.4	19.7	19.9	20.4	20.4
12H	4H	17.0	17.3	17.4	17.7	18.1	17.0	17.3	17.4	17.7	18.1	18.1
	6H	18.2	18.4	18.6	18.9	19.3	18.2	18.4	18.6	18.9	19.3	19.3
	8H	18.8	19.0	19.3	19.5	20.0	18.8	19.0	19.3	19.5	20.0	20.0
Variation of the observer position for the luminaire distances S												
S = 1.0H S = 1.5H S = 2.0H		+1.0 / -0.3 +2.1 / -0.5 +3.2 / -0.8					+1.0 / -0.3 +2.1 / -0.5 +3.2 / -0.8					
Standard table Correction Summand		BK06 3.0					BK06 3.0					
Corrected Glare Indices referring to 477lm Total Luminous Flux												

New construction Plaster Frame S

ARKOSLIGHT

Optional mounting accessory



PRODUCT	
Model	NC PLASTER FRAME S Ø75
Reference	U100-01-09
Category	Optional Mounting Accessory
IC Rated	Yes
Weight	1.13 lb 514 g
Packaged Weight	1.90 lb 864 g
Packaging Dimensions	16.53x8.93x3.15 in 420x227x80 mm
TO BE USED WITH REMOTE BOX	




		PRODUCT
Model		Swap L Add-On Bezel
Colour		W ☐ Matt white
Category		Accessories



Ⓡ 2.95 - 3.11 in (75 - 79 mm)

+



Ⓡ 3.11 - 3.58 in (79 - 91 mm)

Add-on bezel

Accessory always included but for optional use.
It extends the piece's bezel to cover larger recesses, keeping Swap's minimalism and its perfect integration into the ceiling.

Easy to fit. Ideal for reforms to replace the light spot, with the already existing holes, without altering the ceiling or repainting. Swap is the best option for updating to LED technology by means of a real light fixture with incorporated LED, in contrast to just a retrofit lamp that only implies a less efficient update of the light source.