




DIMENSIONS



PRODUCT

Name	SALT 1 UL 3000K NW
Reference	U2200111NW
Color	Black-White
RAL	9005 & 9016
Category	SUSPENSION

LIGHT SOURCE

Type	LED
Gross luminous flux	3545 Lm
Color temperature	3000 K
Chromatic stability	MacAdam Step 2
Color Rendering Index	CRI>90
Power	23 W
Current	600 mA
Efficacy	154 Lm/W
LED lifespan	L80B10>60.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	66%
Delivered luminous flux	2340 Lm
Light beam angle	77°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included: ERP-PSB series or similar
Power values of the system	27 W
Frequency	50/60 Hz
Dimming	0-10V / TRIAC/ELV dimming only at 120V

OTHER DATA

Environmental location	DAMP
Junction box cover	Included. For octagonal Junction box
Junction box cover color	Textured black. Other finishing, please consult
Junction box cover measurements	Ø5.51 in Ø140 mm
Cord Length	10 ft 3.05 m


Awards



High Bay light fitting performance combined with the design of a unique decorative piece. Salt integrates driver and heat dissipation into the design of the fitting itself and achieves on the one hand an excellent thermal management and on the other hand the freedom to hang the fixture at any desired height. And to prevent glare, Salt disposes of a diffusor covering the light source.



DIMENSIONS



Awards




OTHER DATA

Fast adjustment tensioner	Yes
Weight	9.70 lb 4400 gr
Packaged weight	11.31 lb 5129.4 gr
Packaging dimensions	17.80 x 17.80 x 16.46 in 452 x 452 x 418 mm
Materials	Aluminium - Polymethyl Methacrylate




High Bay light fitting performance combined with the design of a unique decorative piece. Salt integrates driver and heat dissipation into the design of the fitting itself and achieves on the one hand an excellent thermal management and on the other hand the freedom to hang the fixture at any desired height. And to prevent glare, Salt disposes of a diffusor covering the light source.

POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR												
p Ceiling		70	70	50	50	30	70	70	50	50	30	
p Walls		50	30	50	30	30	50	30	50	30	30	
p Floor		20	20	20	20	20	20	20	20	20	20	
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
2H	2H	14.3	15.3	14.6	15.5	15.8	14.3	15.3	14.6	15.5	15.8	
	3H	16.1	17.0	16.4	17.3	17.5	16.1	17.0	16.4	17.3	17.5	
	4H	16.8	17.7	17.1	17.9	18.2	16.8	17.7	17.1	17.9	18.2	
	6H	17.3	18.1	17.6	18.4	18.7	17.3	18.1	17.6	18.4	18.7	
	8H	17.5	18.3	17.8	18.6	18.9	17.5	18.3	17.8	18.6	18.9	
4H	12H	17.6	18.4	18.0	18.7	19.0	17.6	18.4	18.0	18.7	19.0	
	2H	14.9	15.8	15.2	16.1	16.3	14.9	15.8	15.2	16.1	16.3	
	3H	16.9	17.7	17.3	18.0	18.3	16.9	17.7	17.3	18.0	18.3	
	4H	17.7	18.4	18.1	18.7	19.1	17.7	18.4	18.1	18.7	19.1	
	6H	18.4	19.0	18.8	19.3	19.7	18.4	19.0	18.8	19.3	19.7	
8H	8H	18.6	19.1	19.0	19.5	19.9	18.6	19.1	19.0	19.5	19.9	
	12H	18.8	19.3	19.2	19.7	20.1	18.8	19.3	19.2	19.7	20.1	
	4H	18.0	18.6	18.5	18.9	19.4	18.0	18.6	18.5	18.9	19.4	
	6H	18.8	19.3	19.3	19.7	20.1	18.8	19.3	19.3	19.7	20.1	
	8H	19.2	19.5	19.6	20.0	20.5	19.2	19.5	19.6	20.0	20.5	
12H	12H	19.4	19.7	19.9	20.2	20.7	19.4	19.7	19.9	20.2	20.7	
	4H	18.1	18.5	18.5	18.9	19.4	18.1	18.5	18.5	18.9	19.4	
	6H	18.9	19.3	19.4	19.7	20.2	18.9	19.3	19.4	19.7	20.2	
	8H	19.3	19.6	19.8	20.1	20.6	19.3	19.6	19.8	20.1	20.6	
Variation of the observer position for the luminaire distances S												
S = 1.0H S = 1.5H S = 2.0H		+0.3 / -0.3 +0.7 / -0.5 +1.3 / -0.8					+0.3 / -0.3 +0.7 / -0.5 +1.3 / -0.8					
Standard table		BK05					BK05					
Correction Summand		-4.1					-4.1					
Corrected Glare Indices referring to 3545lm Total Luminous Flux												