




DIMENSIONS



Name	DEEP MINI UL 2700K WT
Reference	U2500110WT
Color	Textured white
RAL	9016
Category	CEILING RECESSED

Mounting Accessory / Driver	Mandatory, not included. See next page
Model	NC PLASTER FRAME L Ø122 9.5-16.8W 700mA 120-277V
Reference	U1000051

Type	LED
Gross luminous flux	1280 Lm
Color temperature	2700 K
Chromatic stability	MacAdam Step 2
Color Rendering Index	CRI>90
Power	10 W
Current	700 mA
Efficacy	128 Lm/W
LED lifespan	L80B10>60.000h

Lighting efficiency	76%
Delivered luminous flux	973 Lm
Light beam angle	89°

Power values of the system	13 W
Voltage	120-277 V
Frequency	50/60 Hz
Dimming	0-10V / TRIAC dimming only at 120Vac.

IC Rated	Yes
Environmental location	DAMP

PRODUCT

MOUNTING ACCESSORY / DRIVER

LIGHT SOURCE

LIGHTING FIXTURE | PHOTOMETRIC DATA


LIGHTING FIXTURE | ELECTRICAL DATA

OTHER DATA

DEEP is an LED downlight for general lighting functions designed with a recessed diffuser which considerably reduces ceiling brightness.



DIMENSIONS




Recess measurements	Ø4.80 in Ø122 mm
Weight	0.66 lb 300 gr
Packaged weight	0.88 lb 400 gr
Packaging dimensions	8.07 x 6.06 x 3.58 in 205 x 154 x 91 mm
Materials	Aluminium - Polymethyl Methacrylate

OTHER DATA



DEEP is an LED downlight for general lighting functions designed with a recessed diffuser which considerably reduces ceiling brightness.

Mandatory / Not Included




PRODUCT	
Model	NC PLASTER FRAME L Ø122 9.5-16.8W 700mA 120-277V
Driver	Included: APS L9WCD series or similar
Reference	U1000051
IC Rated	Yes
Dimming	0-10V / TRIAC dimming only at 120Vac.
Fast connect	Yes
Size	14.17 - 25 x 14.06 x 4.72 in 360 - 635 x 357 x 120 mm
Weight	4.01 lb 1824 gr
Packaged weight	5.74 lb 2609 gr
Packaging dimensions	16.6 x 15.03 x 4.52 in 422 x 382 x 115 mm
Nº Luminaires	1

INPUT CHARACTERISTICS	
Input Voltage	120-277 V
Frequency	50/60 Hz


OUTPUT CHARACTERISTICS	
Output Voltage	13 - 24 V
Output Current	700 mA
Output Power	9.5 - 16.8 W



POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR												
ρ Ceiling		70	70	50	50	30	70	70	50	50	30	30
ρ Walls		50	30	50	30	30	50	30	50	30	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
2H	2H	22.4	23.5	22.7	23.8	24.0	22.4	23.5	22.7	23.8	24.0	24.0
	3H	23.4	24.5	23.7	24.7	25.0	23.4	24.5	23.7	24.7	25.0	25.0
	4H	23.7	24.7	24.0	25.0	25.2	23.7	24.7	24.0	25.0	25.2	25.2
	6H	23.9	24.8	24.2	25.1	25.4	23.9	24.8	24.2	25.1	25.4	25.4
	8H	24.0	24.8	24.3	25.2	25.5	24.0	24.8	24.3	25.2	25.5	25.5
	12H	24.0	24.9	24.4	25.2	25.5	24.0	24.9	24.4	25.2	25.5	25.5
4H	2H	22.7	23.7	23.1	24.0	24.3	22.7	23.7	23.1	24.0	24.3	24.3
	3H	23.9	24.8	24.3	25.1	25.4	23.9	24.8	24.3	25.1	25.4	25.4
	4H	24.3	25.1	24.7	25.4	25.8	24.3	25.1	24.7	25.4	25.8	25.8
	6H	24.6	25.3	25.0	25.6	26.0	24.6	25.3	25.0	25.6	26.0	26.0
	8H	24.7	25.3	25.2	25.7	26.1	24.7	25.3	25.2	25.7	26.1	26.1
	12H	24.9	25.4	25.3	25.8	26.2	24.9	25.4	25.3	25.8	26.2	26.2
8H	4H	24.4	25.0	24.9	25.4	25.8	24.4	25.0	24.9	25.4	25.8	25.8
	6H	24.8	25.3	25.3	25.7	26.2	24.8	25.3	25.3	25.7	26.2	26.2
	8H	25.0	25.5	25.5	25.9	26.4	25.0	25.5	25.5	25.9	26.4	26.4
	12H	25.2	25.6	25.7	26.1	26.6	25.2	25.6	25.7	26.1	26.6	26.6
12H	4H	24.4	25.0	24.9	25.4	25.8	24.4	25.0	24.9	25.4	25.8	25.8
	6H	24.9	25.3	25.3	25.7	26.2	24.9	25.3	25.3	25.7	26.2	26.2
	8H	25.1	25.5	25.6	25.9	26.4	25.1	25.5	25.6	25.9	26.4	26.4
	12H	25.1	25.5	25.6	25.9	26.4	25.1	25.5	25.6	25.9	26.4	26.4
Variation of the observer position for the luminaire distances S												
S = 1.0H S = 1.5H S = 2.0H		+0.2 / -0.3 +0.4 / -0.8 +1.0 / -1.5					+0.2 / -0.3 +0.4 / -0.8 +1.0 / -1.5					
Standard table		BK03					BK03					
Correction Summand		5.8					5.8					
Corrected Glare Indices referring to 1280lm Total Luminous Flux												