




DIMENSIONS



Awards



PRODUCT

Name	SHOT LIGHT UL 38° 2700K N
Reference	U2681120N
Color	Black
RAL	Color in the mass looks alike RAL 9005
Category	CEILING RECESSED

MOUNTING ACCESSORY / DRIVER

Mounting Accessory / Driver	Mandatory, not included. See next page
Model	REMOTE BOX 5.6-33W 700mA
Reference	U100003602

LIGHT SOURCE

Type	LED
Gross luminous flux	190 Lm
Color temperature	2700 K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>90
Power	2.1 W
Current	700 mA
Efficacy	90 Lm/W
LED lifespan	L90B10>102.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	92%
Delivered luminous flux	175 Lm
Light beam angle	38

LIGHTING FIXTURE | ELECTRICAL DATA

Power values of the system	2.9 W
Voltage	120-277 V
Frequency	50/60 Hz
Dimming	0-10V

OTHER DATA

IC Rated	Yes
Environmental location	DAMP

A luminaire conceived to be a small and discreet point of light in the ceiling, that hides the light source to offer maximum visual comfort. Specifically designed with an anti-glare screen and a micro-reflector, SHOT LIGHT generates a perfectly defined light beam.




Recess measurements	Ø1.50 in Ø38 mm
Weight	0.16 lb 71 gr
Packaged weight	0.21 lb 96 gr
Packaging dimensions	3.03 x 2.75 x 2.08 in 77 x 70 x 53 mm
Materials	Aluminium - Acrylonitrile Butadiene Styrene - Polycarbonate

OTHER DATA



DIMENSIONS




Awards



A luminaire conceived to be a small and discreet point of light in the ceiling, that hides the light source to offer maximum visual comfort. Specifically designed with an anti-glare screen and a micro-reflector, SHOT LIGHT generates a perfectly defined light beam.

Mandatory / Not Included




PRODUCT	
Model	REMOTE BOX 5.6-33W 700mA
Driver	Included
Reference	U100003602
IC Rated	Yes
Dimming	0-10V
Size	7.48 x 3.78 x 1.35 in 190 x 94 x 34 mm
Weight	1.8 lb 820 gr
Packaged weight	1.93 lb 875 gr
Packaging dimensions	9.53 x 4.13 x 1.54 in 242 x 105 x 39 mm
Nº Luminaires	3 to 12
LED - Driver Distance	Maximum suggested distance is 16 feet

INPUT CHARACTERISTICS	
Input Voltage	120-277 V
Frequency	50/60 Hz


OUTPUT CHARACTERISTICS	
Output Voltage	8 - 47 V
Output Current	700 mA
Output Power	5.6 - 33 W






SERIAL CONNECTION FOR SEVERAL FIXTURES TO A SINGLE CONSTANT CURRENT DRIVER
RESPECT THE DISTANCE LED - DRIVER

POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR												
ρ Ceiling		70	70	50	50	30	70	70	50	50	30	
ρ Walls		50	30	50	30	30	50	30	50	30	30	
ρ Floor		20	20	20	20	20	20	20	20	20	20	
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
2H	2H	-4.9	-4.2	-4.6	-4.0	-3.8	-4.7	-4.1	-4.5	-3.9	-3.7	
	3H	-1.1	-0.5	-0.8	-0.3	-0.0	-1.3	-0.7	-1.0	-0.4	-0.2	
	4H	0.7	1.3	1.0	1.5	1.8	0.8	1.4	1.1	1.6	1.9	
	6H	2.9	3.4	3.2	3.6	3.9	3.2	3.7	3.5	3.9	4.2	
	8H	4.2	4.7	4.5	5.0	5.2	4.3	4.8	4.7	5.1	5.4	
12H	5.5	6.0	5.9	6.3	6.6	5.7	6.1	6.0	6.4	6.7		
	4H	2H	-3.7	-3.2	-3.4	-2.9	-2.7	-3.6	-3.1	-3.3	-2.8	-2.6
		3H	0.1	0.6	0.5	0.9	1.2	0.2	0.6	0.5	0.9	1.2
		4H	2.2	2.6	2.5	2.9	3.2	2.4	2.8	2.7	3.1	3.4
		6H	4.5	4.8	4.9	5.2	5.6	4.8	5.2	5.2	5.5	5.9
8H		5.9	6.2	6.3	6.6	7.0	6.1	6.4	6.5	6.8	7.2	
12H	7.4	7.6	7.8	8.0	8.4	7.5	7.8	8.0	8.2	8.6		
	8H	4H	3.2	3.4	3.6	3.8	4.2	3.3	3.6	3.7	4.0	4.4
		6H	5.7	5.9	6.2	6.3	6.8	5.9	6.1	6.4	6.6	7.0
		8H	7.3	7.4	7.7	7.9	8.3	7.4	7.5	7.8	8.0	8.4
		12H	8.9	9.1	9.4	9.5	10.0	9.0	9.2	9.5	9.6	10.1
12H	4H	3.4	3.7	3.8	4.1	4.5	3.5	3.8	4.0	4.2	4.6	
	6H	6.1	6.2	6.5	6.7	7.2	6.3	6.4	6.7	6.9	7.3	
	8H	7.7	7.9	8.2	8.3	8.8	7.8	8.0	8.3	8.4	8.9	
Variation of the observer position for the luminaire distances S												
S = 1.0H S = 1.5H S = 2.0H		+0.4 / -0.2 +0.9 / -0.5 +1.6 / -0.6					+0.4 / -0.2 +0.9 / -0.4 +1.6 / -0.6					
Standard table		---					---					
Correction Summand		---					---					
Corrected Glare Indices referring to 190lm Total Luminous Flux												