




DIMENSIONS



Name	REC MINI UL 3000K NT
Reference	U3080011NT
Color	Textured black
RAL	9005
Category	WALL & FLOOR LIGHTS

PRODUCT

Type	LED
Gross luminous flux	2650 Lm
Color temperature	3000 K
Chromatic stability	MacAdam Step 2
Color Rendering Index	CRI>90
Power	20 W
Current	700 mA
Efficacy	133 Lm/W
LED lifespan	L80B10>60.000h

LIGHT SOURCE

Lighting efficiency	75%
Delivered luminous flux	1988 Lm

LIGHTING FIXTURE | PHOTOMETRIC DATA

Driver	Included: ERP-PSB series or similar
Power values of the system	23 W
Frequency	50/60 Hz
Dimming	0-10V / TRIAC/ELV dimming only at 120V

LIGHTING FIXTURE | ELECTRICAL DATA


Environmental location	DAMP
Junction box cover	Included. For octagonal Junction box
Junction box cover color	Textured white. Other finishing, please consult
Junction box cover measurements	Ø4.33 in Ø110 mm
Weight	2.37 lb 1073 gr
Packaged weight	2.53 lb 1148 gr
Packaging dimensions	9.13 x 7.48 x 1.89 in 232 x 190 x 48 mm
Materials	Aluminium - Polymethyl Methacrylate

OTHER DATA



REC is an LED luminaire ideal for indirect lighting applications. A perfect fit for projects that give priority to the comfort of indirect light but also require a high volume of lumens. REC is a finest cuboid with pure lines and a minimalist design.

POLAR DIAGRAM



CONICAL DIAGRAM

