




DIMENSIONS



Name	REC MINI UL 4000K NT
Reference	U3080012NT
Color	Textured black
RAL	9005
Category	WALL & FLOOR LIGHTS

PRODUCT

Name	REC MINI UL 4000K NT
Reference	U3080012NT
Color	Textured black
RAL	9005
Category	WALL & FLOOR LIGHTS

LIGHT SOURCE

Type	LED
Gross luminous flux	2700 Lm
Color temperature	4000 K
Chromatic stability	MacAdam Step 2
Color Rendering Index	CRI>90
Power	20 W
Current	700 mA
Efficacy	135 Lm/W
LED lifespan	L80B10>60.000h

LED

2700 Lm

4000 K

MacAdam Step 2

CRI>90

20 W

700 mA

135 Lm/W

L80B10>60.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	75%
Delivered luminous flux	2025 Lm

75%

2025 Lm

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included: ERP-PSB series or similar
Power values of the system	23 W
Frequency	50/60 Hz
Dimming	0-10V / TRIAC/ELV dimming only at 120V

Included: ERP-PSB series or similar

23 W

50/60 Hz

0-10V / TRIAC/ELV dimming only at 120V

OTHER DATA

Environmental location	DAMP
Junction box cover	Included. For octagonal Junction box
Junction box cover color	Textured white. Other finishing, please consult
Junction box cover measurements	Ø4.33 in Ø110 mm
Weight	2.37 lb 1073 gr
Packaged weight	2.53 lb 1148 gr
Packaging dimensions	9.13 x 7.48 x 1.89 in 232 x 190 x 48 mm
Materials	Aluminium - Polymethyl Methacrylate

DAMP

Included. For octagonal Junction box

Textured white. Other finishing, please consult

Ø4.33 in | Ø110 mm

2.37 lb | 1073 gr

2.53 lb | 1148 gr


9.13 x 7.48 x 1.89 in | 232 x 190 x 48 mm

Aluminium - Polymethyl Methacrylate



REC is an LED luminaire ideal for indirect lighting applications. A perfect fit for projects that give priority to the comfort of indirect light but also require a high volume of lumens. REC is a finest cuboid with pure lines and a minimalist design.

POLAR DIAGRAM



CONICAL DIAGRAM

