




DIMENSIONS



Awards



INTERIOR DESIGN

PRODUCT

Name	BLACK FOSTER REC 2 UL SPOT 2700K WN
Reference	U3192110WN
Color	White-Black
RAL	Colour in the mass looks alike RAL 9016 & 9005
Category	CEILING RECESSED

MOUNTING ACCESSORY / DRIVER

Mounting Accessory / Driver	Mandatory, not included. See next page
Model	REMOTE BOX 3.6-22W 450mA
Reference	U100011802

LIGHT SOURCE

Type	LED
Gross luminous flux	260 Lm
Color temperature	2700 K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>90
Power	2.7 W
Current	450 mA
Efficacy	96 Lm/W
LED lifespan	L90B10>102.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	90%
Delivered luminous flux	234 Lm
Light beam angle	19

LIGHTING FIXTURE | ELECTRICAL DATA

Power values of the system	3.7 W
Voltage	120-277 V
Frequency	50/60 Hz
Dimming	0-10V


OTHER DATA

IC Rated	Yes
Environmental location	DAMP
Weight	0.31 lb 140 gr
Packaged weight	0.47 lb 217 gr
Packaging dimensions	6.22 x 3.85 x 1.96 in 158 x 98 x 50 mm
Materials	Aluminium / Acrylonitrile Butadiene Styrene



Black Foster is the product that transfers the claimed effect "The Invisible Black" to a recessed-isolated lineal luminary; also available in trimless version. If we take a closer view to the recessed model, its bezel is so thin than when lighted up, it is unperceived; offering an aesthetic of "visual trimless". Black Foster stands out for its refinement, its visual comfort and for almost completely hide the source of light from the human eye range.

Mandatory / Not Included




PRODUCT	
Model	REMOTE BOX 3.6-22W 450mA
Driver	Included
Reference	U100011802
IC Rated	Yes
Dimming	0-10V
Size	7.48 x 3.78 x 1.35 in 190 x 94 x 34 mm
Weight	1.8 lb 820 gr
Packaged weight	1.93 lb 875 gr
Packaging dimensions	9.53 x 4.13 x 1.54 in 242 x 105 x 39 mm
Nº Luminaires	2 to 7
LED - Driver Distance	Maximum suggested distance is 16 feet

INPUT CHARACTERISTICS	
Input Voltage	120-277 V
Frequency	50/60 Hz


OUTPUT CHARACTERISTICS	
Output Voltage	8 - 49 V
Output Current	450 mA
Output Power	3.6 - 22 W






SERIAL CONNECTION FOR SEVERAL FIXTURES TO A SINGLE CONSTANT CURRENT DRIVER
RESPECT THE DISTANCE LED - DRIVER

POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR											
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	2.9	3.5	3.1	3.7	3.9	2.6	3.2	2.8	3.4	3.6
	3H	6.6	7.2	6.9	7.4	7.7	6.1	6.7	6.4	6.9	7.2
	4H	8.5	9.1	8.8	9.3	9.6	8.1	8.7	8.4	9.0	9.2
	6H	10.5	11.1	10.9	11.4	11.6	10.2	10.7	10.5	11.0	11.3
	8H	11.6	12.2	12.0	12.5	12.8	11.5	12.0	11.8	12.3	12.6
	12H	13.0	13.5	13.3	13.8	14.1	12.8	13.3	13.1	13.6	13.9
4H	2H	3.9	4.5	4.2	4.8	5.0	3.7	4.3	4.0	4.6	4.8
	3H	7.8	8.3	8.2	8.6	8.9	7.5	8.0	7.9	8.3	8.6
	4H	9.9	10.3	10.2	10.6	11.0	9.7	10.1	10.0	10.4	10.8
	6H	12.1	12.5	12.5	12.9	13.2	11.9	12.2	12.3	12.6	13.0
	8H	13.4	13.7	13.8	14.1	14.5	13.3	13.6	13.7	14.0	14.4
	12H	14.8	15.1	15.2	15.5	15.9	14.7	15.0	15.1	15.4	15.8
8H	4H	10.7	11.0	11.1	11.4	11.8	10.5	10.8	10.9	11.2	11.6
	6H	13.2	13.5	13.7	13.9	14.4	13.1	13.3	13.5	13.7	14.2
	8H	14.6	14.8	15.1	15.3	15.8	14.6	14.8	15.1	15.2	15.7
	12H	16.3	16.4	16.8	16.9	17.4	16.2	16.4	16.7	16.8	17.3
12H	4H	11.0	11.2	11.4	11.6	12.0	10.8	11.1	11.2	11.5	11.9
	6H	13.6	13.8	14.1	14.3	14.7	13.5	13.7	13.9	14.1	14.6
	8H	15.1	15.3	15.6	15.7	16.2	15.1	15.2	15.5	15.7	16.2
Variation of the observer position for the luminaire distances S											
S = 1.0H		+0.2 / -0.1					+0.2 / -0.2				
S = 1.5H		+0.3 / -0.3					+0.3 / -0.3				
S = 2.0H		+0.5 / -0.5					+0.5 / -0.5				
Standard table		---					---				
Correction		---					---				
Summand		---					---				
Corrected Glare Indices referring to 260lm Total Luminous Flux											