


Black Foster Suspension

ARKOSLIGHT



DIMENSIONS



PRODUCT

Name	BLACK FOSTER SUSP 1200 UL SPOT 3500K WT
Reference	U3211113WT
Color	Textured white
RAL	9016
Category	SUSPENSION

LIGHT SOURCE

Type	LED
Gross luminous flux	2300 Lm
Color temperature	3500 K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>90
Power	21 W
Current	700 mA
Efficacy	109 Lm/W
LED lifespan	L90B10>102.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	90%
Delivered luminous flux	2070 Lm
Light beam angle	19°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included: ERP-PSB series or similar
Power values of the system	24 W
Frequency	50/60 Hz
Dimming	0-10V / TRIAC/ELV dimming only at 120V

OTHER DATA

Environmental location	DAMP
Junction box cover	Included. For octagonal Junction box
Junction box cover color	Textured white. Other finishing, please consult
Junction box cover measurements	Ø5.51 in Ø140 mm
Cord Length	MAX. 10 ft MAX. 3.05 m

Awards




Black Foster Suspension is the product that transfers the claimed effect "The Invisible Black" to a linear suspended system. It is composed by a series of modules which combine light emissions with dark segments. Nevertheless, whether it is On or Off, Black Foster always preserves the aesthetic of a perfect dark line.

Black Foster Suspension

ARKOSLIGHT



DIMENSIONS



Fast adjustment tensioner

Weight

Packaged weight

Packaging dimensions

Materials

OTHER DATA

Yes

7.18 lb | 3255 gr

9.85 lb | 4470 gr

Ø6.10x50.00 in | Ø155x1270 mm

Aluminium - Acrylonitrile Butadiene Styrene - Polycarbonate




Awards




Black Foster Suspension is the product that transfers the claimed effect "The Invisible Black" to a linear suspended system. It is composed by a series of modules which combine light emissions with dark segments. Nevertheless, whether it is On or Off, Black Foster always preserves the aesthetic of a perfect dark line.



POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR												
ρ Ceiling		70	70	50	50	30	70	70	50	50	30	30
ρ Walls		50	30	50	30	30	50	30	50	30	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
2H	2H	-0.1	0.6	0.2	0.8	1.0	0.5	1.1	0.7	1.3	1.5	1.5
	3H	3.1	3.7	3.4	4.0	4.2	3.9	4.5	4.2	4.8	5.0	5.0
	4H	5.0	5.5	5.3	5.8	6.0	5.9	6.5	6.2	6.7	7.0	7.0
	6H	7.0	7.6	7.4	7.8	8.1	8.1	8.7	8.4	8.9	9.2	9.2
	8H	8.1	8.6	8.5	8.9	9.2	9.4	9.9	9.7	10.2	10.5	10.5
	12H	9.5	10.0	9.8	10.3	10.6	10.8	11.3	11.1	11.6	11.9	11.9
4H	2H	1.2	1.8	1.5	2.0	2.3	1.6	2.1	1.9	2.4	2.6	2.6
	3H	4.6	5.1	4.9	5.4	5.7	5.2	5.7	5.6	6.0	6.3	6.3
	4H	6.6	7.0	7.0	7.3	7.7	7.3	7.8	7.7	8.1	8.4	8.4
	6H	8.8	9.1	9.2	9.5	9.9	9.7	10.1	10.1	10.4	10.8	10.8
	8H	10.0	10.3	10.4	10.7	11.1	11.0	11.4	11.5	11.7	12.1	12.1
	12H	11.4	11.7	11.8	12.1	12.5	12.6	12.9	13.0	13.3	13.7	13.7
8H	4H	7.5	7.8	7.9	8.2	8.6	8.1	8.4	8.5	8.8	9.2	9.2
	6H	9.9	10.1	10.3	10.5	11.0	10.7	10.9	11.1	11.3	11.8	11.8
	8H	11.3	11.5	11.7	11.9	12.4	12.2	12.4	12.7	12.8	13.3	13.3
	12H	12.9	13.1	13.4	13.5	14.0	13.9	14.1	14.4	14.6	15.0	15.0
12H	4H	7.8	8.0	8.2	8.4	8.9	8.3	8.5	8.7	8.9	9.4	9.4
	6H	10.3	10.5	10.7	10.9	11.4	10.9	11.1	11.4	11.6	12.1	12.1
	8H	11.8	11.9	12.3	12.4	12.9	12.6	12.7	13.1	13.2	13.7	13.7
Variation of the observer position for the luminaire distances S												
S = 1.0H S = 1.5H S = 2.0H		+0.2 / -0.1 +0.3 / -0.3 +0.5 / -0.5					+0.2 / -0.1 +0.3 / -0.3 +0.5 / -0.5					
Standard table		---					---					
Correction Summand		---					---					
Corrected Glare Indices referring to 2300lm Total Luminous Flux												