




DIMENSIONS



Awards



Name	BLACK FOSTER MICRO RECESSED 3 UL 3500K N
Reference	U4141013N
Color	Matt black
RAL	9005
Category	CEILING RECESSED

Type	LED
Gross luminous flux	Depending on Mounting Accessories Lm
Color temperature	3500 K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>90
Power	Depending on Mounting Accessories W
Current	Depending on Mounting Accessories mA
LED lifespan	L90B10>60.000h

Lighting efficiency	87%
Light beam angle	37°


Driver	Requires remote driver
Power values of the system	Depending on Mounting Accessories W
Frequency	Depending on Mounting Accessories
Dimming	Depending on Mounting Accessories

IC Rated	Yes
Environmental location	DAMP
Recess measurements	0.94 x 2.36 in in 24 x 60 mm
Weight	0.12 lb 55 gr
Packaged weight	0.25 lb 116 gr
Packaging dimensions	6.92 x 2.4 x 1.96 in 176 x 61 x 50 mm
Materials	Aluminium - Acrylonitrile Butadiene Styrene - Polycarbonate




Black Foster Micro is a feat of engineering which brings the acclaimed "The Invisible Black" effect to a hyper-reduced light. Its tiny size and thin trim offer a "trimless visual" aesthetic which combines with its almost imperceptible presence as a result of its compact dimensions. Black Foster Micro is designed for general or accent lighting and can be used in projects that seek ceiling lighting that plays a minimal role.

POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR											
p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	8.4	9.0	8.6	9.2	9.4	8.2	8.8	8.5	9.0	9.2
	3H	8.3	8.9	8.6	9.1	9.4	8.2	8.8	8.5	9.0	9.2
	4H	8.4	9.0	8.7	9.2	9.5	8.2	8.8	8.5	9.0	9.3
	6H	8.7	9.2	9.0	9.4	9.7	8.4	8.9	8.7	9.1	9.4
	8H	8.8	9.3	9.2	9.6	9.9	8.5	9.0	8.8	9.3	9.6
	12H	9.2	9.6	9.5	9.9	10.2	8.8	9.3	9.2	9.6	9.9
4H	2H	8.2	8.7	8.5	9.0	9.2	8.0	8.6	8.3	8.8	9.1
	3H	8.2	8.7	8.6	9.0	9.3	8.1	8.5	8.4	8.8	9.1
	4H	8.4	8.8	8.7	9.1	9.4	8.2	8.6	8.5	8.9	9.2
	6H	8.8	9.2	9.2	9.5	9.9	8.5	8.8	8.9	9.2	9.6
	8H	9.1	9.4	9.6	9.8	10.2	8.8	9.0	9.2	9.4	9.8
	12H	9.7	9.9	10.1	10.3	10.8	9.3	9.5	9.7	9.9	10.3
8H	4H	8.4	8.7	8.8	9.1	9.5	8.2	8.5	8.6	8.9	9.3
	6H	9.0	9.2	9.5	9.7	10.1	8.7	8.9	9.1	9.3	9.8
	8H	9.5	9.7	10.0	10.1	10.6	9.1	9.3	9.6	9.7	10.2
	12H	10.3	10.4	10.8	10.9	11.4	9.9	10.0	10.4	10.5	11.0
12H	4H	8.4	8.7	8.8	9.1	9.5	8.2	8.5	8.6	8.9	9.3
	6H	9.1	9.3	9.6	9.7	10.2	8.8	8.9	9.2	9.4	9.9
	8H	9.6	9.8	10.1	10.2	10.7	9.3	9.4	9.8	9.9	10.4
Variation of the observer position for the luminaire distances S											
S = 1.0H		+4.7 / -2.2					+4.9 / -2.4				
S = 1.5H		+7.4 / -2.5					+7.6 / -2.7				
S = 2.0H		+9.4 / -2.8					+9.7 / -3.4				
Standard table		---					---				
Correction		---					---				
Summand		---					---				
Corrected Glare Indices referring to 315lm Total Luminous Flux											