




DIMENSIONS



PRODUCT

Name	LOOP 1300 UL 5M 3000K BG
Reference	U4731201BG
Color	Brushed Gold
RAL	Paint of metallic nanoparticles
Category	SUSPENSION

MOUNTING ACCESSORY / DRIVER

Mounting Accessory / Driver	Mandatory, not included. See next page
Model	REMOTE BOX 19.6-26.4W 700mA
Reference	U1000137

LIGHT SOURCE

Type	LED
Gross luminous flux	3070 Lm
Color temperature	3000 K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>95
Power	24.6 W
Current	700 mA
Efficacy	125 Lm/W
LED lifespan	L90B10>50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	38%
Delivered luminous flux	1167 Lm
Light beam angle	110°

LIGHTING FIXTURE | ELECTRICAL DATA

Power values of the system	28.1 W
Voltage	120-277 V
Frequency	50/60 Hz
Dimming	0-10V

OTHER DATA

IC Rated	Yes
Environmental location	DAMP

Awards



reddot winner 2023
lighting design

archiproducts
AWARDS
WINNER

light
MIDDLE EAST
AWARDS
2025

Daring and fanciful, Loop appeals to industrial lyricism with a design inspired by electrical insulators. The protagonist of the decoration, its body is a sequence of light disks with an aluminium interior. It's adorned by a suspended glass cylinder that acts as a fastflowing, controlled source of projected light.




Recess measurements	Ø2.44 in Ø62 mm
Cord Length	MAX. 16.4 ft MAX. 5 m
Fast adjustment tensioner	No
Weight	6.59 lb 2987 gr
Packaged weight	10.99 lb 4987 gr
Packaging dimensions	Ø5 x 64.76 in Ø127 x 1645 mm
Materials	Optical glass / Optical Polymethyl Methacrylate

OTHER DATA



DIMENSIONS



Awards




reddot winner 2023
lighting design

archiproducts
AWARDS
WINNER

light
MIDDLE EAST
AWARDS
2025

Daring and fanciful, Loop appeals to industrial lyricism with a design inspired by electrical insulators. The protagonist of the decoration, its body is a sequence of light disks with an aluminium interior. It's adorned by a suspended glass cylinder that acts as a fastflowing, controlled source of projected light.

Mandatory / Not Included




PRODUCT	
Model	REMOTE BOX 19.6-26.4W 700mA
Driver	Included
Reference	U1000137
IC Rated	Yes
Dimming	0-10V
Size	7.48 x 2.52 x 1.38 in 190 x 64 x 35 mm
Weight	1.59 lb 720 gr
Packaged weight	1.93 lb 875 gr
Packaging dimensions	11.26 x 2.91 x 1.77 in 286 x 74 x 45 mm
Nº Luminares	1
LED - Driver Distance	Maximum suggested remote mounting distance is 24 feet

INPUT CHARACTERISTICS	
Input Voltage	120-277 V
Frequency	50/60 Hz


OUTPUT CHARACTERISTICS	
Output Voltage	28 - 42 V
Output Current	700 mA
Output Power	19.6 - 26.4 W





SERIAL CONNECTION FOR SEVERAL FIXTURES TO A SINGLE CONSTANT CURRENT DRIVER
RESPECT THE DISTANCE LED - DRIVER

POLAR DIAGRAM



CONICAL DIAGRAM

