




DIMENSIONS



Name	BUDDY TW UL 2700K-5000K FLOOD NG
Reference	U5070138NG
Color	Black-Gold
RAL	9005 & 1036
Category	CEILING RECESSED

PRODUCT

Mounting Accessory / Driver	Mandatory, not included. See next page
Model	REMOTE BOX 2-12.1W 250mA
Reference	U1000127

MOUNTING ACCESSORY / DRIVER

Type	LED
Gross luminous flux	485 Lm
Color temperature	2700 - 5000 K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>90
Power	4 W
Current	250 mA
Efficacy	121 Lm/W
LED lifespan	L80B10>55.000h

LIGHT SOURCE

Lighting efficiency	73%
Delivered luminous flux	354 Lm
Light beam angle	55°

LIGHTING FIXTURE | PHOTOMETRIC DATA

Power values of the system	6.1 W
Voltage	120-277 V
Frequency	50/60 Hz
Dimming	0-10V

LIGHTING FIXTURE | ELECTRICAL DATA

IC Rated	Yes
Environmental location	DAMP

OTHER DATA

The sophistication of recessed lighting. Buddy is here to maximise the luminous performance of the classic recessed luminaire. It emerges with a solid and purposeful design, greater energy savings and excellent visual comfort. The product family comes in several versions with four opening angles -flood, medium, spot and super spot-. The dim to warm technology enables Buddy to facilitate comfort to the space by dimming the intensity and colour temperature. Furthermore, with the tunable White feature it can be controlled independently. Its four versions per position demonstrate its versatility: recessed, trimless, tilt and the tilt trimless version, which maintains its light output at all opening angles.




Recess measurements	Ø3.11 in Ø79 mm
Weight	0.386 lb 175 gr
Packaged weight	0.542 lb 246 gr
Packaging dimensions	5.47 x 4.13 x 3.54 in 139 x 105 x 90 mm
Materials	Aluminium / Polycarbonate / Polymethyl Methacrylate

OTHER DATA




DIMENSIONS



The sophistication of recessed lighting. Buddy is here to maximise the luminous performance of the classic recessed luminaire. It emerges with a solid and purposeful design, greater energy savings and excellent visual comfort. The product family comes in several versions with four opening angles -flood, medium, spot and super spot-. The dim to warm technology enables Buddy to facilitate comfort to the space by dimming the intensity and colour temperature. Furthermore, with the tunable White feature it can be controlled independently. Its four versions per position demonstrate its versatility: recessed, trimless, tilt and the tilt trimless version, which maintains its light output at all opening angles.

Mandatory / Not Included



PRODUCT	
Model	REMOTE BOX 2-12.1W 250mA
Driver	Included
Reference	U1000127
IC Rated	Yes
Dimming	0-10V
Size	7.48 x 3.78 x 1.35 in 190 x 94 x 34 mm
Weight	1.73 lb 785 gr
Packaged weight	1.93 lb 875 gr
Packaging dimensions	9.53 x 4.13 x 1.54 in 242 x 105 x 39 mm
Nº Luminaires	1
LED - Driver Distance	Maximum suggested distance is 16 feet

INPUT CHARACTERISTICS	
Input Voltage	120-277 V
Frequency	50/60 Hz


OUTPUT CHARACTERISTICS	
Output Voltage	8 - 54 V
Output Current	250 mA
Output Power	2 - 12.1 W






SERIAL CONNECTION FOR SEVERAL FIXTURES TO A SINGLE CONSTANT CURRENT DRIVER
RESPECT THE DISTANCE LED - DRIVER

POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR												
ρ Ceiling		70	70	50	50	30	70	70	50	50	30	30
ρ Walls		50	30	50	30	30	50	30	50	30	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
2H	2H	11.7	12.4	11.9	12.6	12.8	11.7	12.5	12.0	12.7	12.9	12.9
	3H	13.4	14.1	13.7	14.3	14.6	13.5	14.1	13.7	14.4	14.6	14.6
	4H	14.1	14.7	14.4	15.0	15.2	14.1	14.8	14.4	15.0	15.3	15.3
	6H	14.6	15.2	14.9	15.4	15.7	14.6	15.2	15.0	15.5	15.8	15.8
	8H	14.8	15.3	15.1	15.6	15.9	14.8	15.4	15.2	15.7	16.0	16.0
	12H	14.9	15.4	15.2	15.7	16.0	15.0	15.5	15.3	15.8	16.1	16.1
4H	2H	12.3	12.9	12.6	13.2	13.4	12.3	13.0	12.6	13.2	13.5	13.5
	3H	14.2	14.8	14.6	15.1	15.4	14.3	14.8	14.6	15.1	15.4	15.4
	4H	15.0	15.5	15.4	15.8	16.2	15.1	15.5	15.4	15.9	16.2	16.2
	6H	15.6	16.0	16.0	16.4	16.8	15.7	16.1	16.1	16.5	16.8	16.8
	8H	15.9	16.2	16.3	16.6	17.0	15.9	16.3	16.4	16.7	17.1	17.1
	12H	16.1	16.4	16.5	16.8	17.2	16.1	16.4	16.6	16.8	17.3	17.3
8H	4H	15.3	15.7	15.7	16.0	16.4	15.3	15.7	15.8	16.1	16.5	16.5
	6H	16.1	16.4	16.5	16.8	17.2	16.1	16.4	16.6	16.8	17.3	17.3
	8H	16.4	16.6	16.9	17.1	17.5	16.5	16.7	16.9	17.1	17.6	17.6
	12H	16.7	16.9	17.1	17.3	17.8	16.7	16.9	17.2	17.4	17.9	17.9
12H	4H	15.3	15.6	15.8	16.0	16.5	15.4	15.7	15.8	16.1	16.5	16.5
	6H	16.2	16.4	16.6	16.8	17.3	16.2	16.4	16.7	16.9	17.3	17.3
	8H	16.5	16.7	17.0	17.2	17.7	16.6	16.8	17.0	17.2	17.7	17.7
	12H	16.5	16.7	17.0	17.2	17.7	16.6	16.8	17.0	17.2	17.7	17.7
Variation of the observer position for the luminaire distances S												
S = 1.0H		+2.6 / -1.5					+2.6 / -1.5					
S = 1.5H		+4.7 / -1.7					+4.7 / -1.7					
S = 2.0H		+6.5 / -2.1					+6.5 / -2.0					
Standard table		BK03					BK03					
Correction Summand		1.5					1.5					
Corrected Glare Indices referring to 485lm Total Luminous Flux												